
500.1095.04

1095 EN3 Overhead Door Closer







Product Specification

Slim 'softline' cover and matching armset Figure 66' bracket included for parallel arm fitting All fixings included for installation Suitable for 30minute and 60minute fire doors Full fitting instructions included with each unit

Specification

Finish Polished Chrome Power Size EN3 Max Door Width 930mm Max Door Weight 60kg Mechanism Rack and Pinion Adjustable Latching Action Yes Adjustable Closing Speed Yes Opening Angle 180 degrees Fire Rated FD30/FD60 Fire Tested BS EN 1634	•	
Power Size EN3 Max Door Width 930mm Max Door Weight 60kg Mechanism Rack and Pinion Adjustable Latching Action Yes Adjustable Closing Speed Yes Opening Angle 180 degrees Fire Rated FD30/FD60 Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Brand	RUTLAND
Max Door Width Max Door Weight 60kg Mechanism Rack and Pinion Adjustable Latching Action Yes Adjustable Closing Speed Yes Opening Angle 180 degrees Fire Rated FD30/FD60 Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Finish	Polished Chrome
Max Door Weight Mechanism Rack and Pinion Adjustable Latching Action Yes Adjustable Closing Speed Yes Opening Angle 180 degrees Fire Rated FD30/FD60 BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Power Size	EN3
Mechanism Rack and Pinion Adjustable Latching Action Yes Adjustable Closing Speed Yes Opening Angle 180 degrees Fire Rated FD30/FD60 Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Max Door Width	930mm
Adjustable Latching Action Yes Adjustable Closing Speed Yes Opening Angle 180 degrees Fire Rated FD30/FD60 Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Max Door Weight	60kg
Adjustable Closing Speed Opening Angle 180 degrees Fire Rated FD30/FD60 Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Mechanism	Rack and Pinion
Opening Angle 180 degrees Fire Rated FD30/FD60 Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Adjustable Latching Action	Yes
Fire Rated FD30/FD60 Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Adjustable Closing Speed	Yes
Fire Tested BS EN 1634 Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Opening Angle	180 degrees
Performance Tested BS EN 1154 Our most popular medium-duty door closer, suitable for general commercial applications,	Fire Rated	FD30/FD60
Our most popular medium-duty door closer, suitable for general commercial applications,	Fire Tested	BS EN 1634
	Performance Tested	BS EN 1154