

810.2300.11

Eclisse Fire Rated Classic Single Pocket Door System - 926 x 2040mm - FD30 **WELLING** Making Ironmongery Easy



Product Specification

- Complete with special jamb/architrave kit made from hard wood, pre-treated with intumescent primer.
- For use with 44mm FD30 rated fire doors (not included)
- Maintenance-free track and runners.
- Fully adjustable front and rear doorstop.
- Runners are tested to 100,000 cycles (that's around 25 years of average use!)
- Anti-warp door profile
- Self-centering floor guide
- 15 year manufacturers guarantee
- Fully tested and approved by International Fire Consultants PAR/10057/01 Revision B
- Max door panel weight: Up to 100Kg without the self-closing device (40kg with self-closing device)
- Channels routed out in jambs to accept standard 15 x 4mm graphite based intumescent seals available separately
- Finished Wall Thickness: 100mm
- Designed for use with 12.5 mm fireboard (not supplied).

Specification

Finish	Silver
Brand	ECLISSE
Door Size	926 x 2040 x 44mm
Max Door Weight	100kg without self-closer, 40kg with self-closer
Finished Wall Thickness	100mm
Fire Rated	Yes - FD30

For more information please contact

01451 824110 | sales@wellinguk.com | www.wellinguk.com

Welling Ironmongery Ltd, Unit R1, Bourton Industrial Park, Bourton on the Water GL54 2HQ