

609 BALL BEARING BUTT HINGE - GRADE 13 - SQUARE CORNERS

OVERVIEW

Intumescent hinge pads should be used when installing on fire doors
 To achieve FD30 or FD60 and comply with fire test evidence – 2 x 0.8mm hinge pads per hinge.
 One Intumescent hinge pad to be behind frame hinge leaf and one behind door hinge leaf
 10-year mechanical guarantee – 200,000 cycles
 Sold as pack of 3nr with screws
 BS EN 1634 fire tested. BS EN 1935: 2002. CE Marked
 Grade 13



SPECIFICATION

Product Code	Finish	Size	Max Door Weight	Fire Rated	Sold as
550.6095.01	Satin Stainless Steel	102 x 76 x 3mm	120kg Adjusted Weight (3 hinges)	FD30 / FD60	Pack of 3
550.6095.02	Polished Stainless Steel				
550.6095.03	Polished Brass				
550.6095.14	Antique Brass				
550.6095.26	Bronze				
550.6095.39	Black				
550.6095.72	White				
550.6095.76	Satin Brass				

PRODUCT FINISHES



Satin Stainless Steel .01 Polished Stainless Steel .02 Electro Plated Brass .03



Antique Brass Plated .14 Dark Bronze Plated .26 Matt Black .39



Matt White .72 Satin Brass Plated .76

TECHNICAL

